

**SPECIFICATION**  
**(Sprint Docket No. 1680)**

**TO ALL WHOM IT MAY CONCERN:**

Be it known that we, **John KULLMAN**, a citizen of the United States and resident of Olathe, Kansas, **Jared A. BOHNDORF**, a citizen of the United States and resident of Olathe, Kansas, and **Rick HAUGHT**, a citizen of the United States and a resident of Lawrence, Kansas, have invented a new and useful:

**METHOD AND SYSTEM FOR  
COMMUNICATING LOCATION  
IN A CELLULAR WIRELESS SYSTEM**

the following of which is a specification.

0  
1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187

## **BACKGROUND**

### **1. Field of the Invention**

The present invention relates to mobile communications and, more particularly, to methods and systems for communicating location in a cellular wireless communication system.

### **2. Description of Related Art**

Cellular wireless is an increasingly popular means of personal communication in the modern world. In a cellular wireless network, a coverage area is divided into a number of sectors defined by radiation patterns from base stations. A mobile station, such as a cellular telephone, personal digital assistant ("PDA"), cellular modem, or other such device, may then communicate with the base station via a radio frequency air interface. In turn, each base station is typically coupled with other access equipment, such as a gateway or switch, to provide connectivity with a transport network such as the public switched telephone network ("PSTN") or the Internet. A person using a mobile station can thereby communicate over the transport network from virtually any place inside the cellular coverage area.

An important feature of contemporary cellular wireless networks is an ability to locate the geographical position of a mobile station. Such a feature was initially developed to assist emergency services in locating a mobile station. For example, in the United States, the Federal Communications Commission ("FCC") has mandated the implementation of "Enhanced 911" ("E911") services, which includes a requirement for cellular wireless carriers to report mobile station location to a public safety access point ("PSAP") when connecting a call from a mobile station to the PSAP.

The E911 mandate was divided into two phases. According to Phase 1, a cellular wireless carrier must identify the location of a mobile 911 caller with an accuracy of the sector in which the caller is located. According to Phase 2 (as now incorporated in Industry Standard TIA/EIA/IS-J-STD-036 (J-STD-036), entitled "Enhanced Wireless 9-1-1, Phase 2), a cellular carrier must identify the location of a mobile 911 caller with an accuracy of at least 50 or 100 meters, depending on the mechanism used to determine location.

In order to comply with Phase 2, a wireless carrier can use network-based positioning mechanisms (such as triangularization techniques, etc.) or handset-based positioning mechanisms (such as GPS), or a combination of both. Unfortunately, however, many carriers are

not yet equipped with the necessary positioning technology, and it will be some time before all or even most mobile stations are equipped with GPS positioning technology or before cellular carriers will be able to locate all mobile stations with the necessary degree of granularity. Consequently, many carriers have focused principally on compliance with Phase 1 of the mandate.

Most carriers can readily comply with Phase 1, because a carrier usually maintains in a home location register ("HLR") or other profile store an indication of the sector in which each active mobile station is operating. Thus, when a carrier receives a 911 call from a mobile station, the carrier can refer to the profile store in order to identify the sector where the mobile station is operating. The carrier can then set up the call to a 911 service center (as PSAP) and provide the center with an indication of that sector. Typically, the carrier will give the PSAP an indication of (i) the geographic position or street address of the base station tower and (ii) the azimuth (angle) at which the sector extends from the base station tower. Emergency service personnel can then work to locate the caller in that general direction from the base station tower.

Emergency services are thus one sort of "location-based service," as they can use a location as a basis to provide a service. In particular, knowing the geographic location of the sector from which a mobile emergency call originates, the emergency service can seek to locate and assist the caller.

The availability of location information to support E911 services has given rise to the development of many other location-based services as well. For instance, given the location of a mobile station, a location-based service provider (e.g., a wireless cellular carrier or third party) can provide the mobile station user with a weather or traffic report in the user's vicinity. As another example, a location-based service provider can report a list of services or establishments (e.g., restaurants, parks, theatres, etc.) in the user's vicinity. As still another example, a location-based service provider can provide a mobile station user with a map of the user's location or with directions for travel between the user's location and another location. And as yet another example, knowing that a mobile station is operating in a particular location, a location-based service provider can send the mobile station a location-based message, such as an advertisement or coupon for a nearby establishment. Other location-based services exist currently or will be developed in the future as well.

Just as a cellular wireless carrier can provide a PSAP with an indication of where a mobile station is located, the carrier can provide other location-based service providers with an indication of where a mobile station is located. For instance, when connecting a call from a mobile station to a location-based service platform (or otherwise being involved with a communication session with a location-based service), the carrier can transmit to the service platform an indication of the sector in which the mobile station is currently operating. As with E911 service, the carrier might provide the geographic coordinates or street address of the sector's base station tower together with an azimuth of the sector. Alternatively, the carrier might translate the base station location into a postal zip code and report that postal zip code to the location-based service provider. The location-based service provider may then perform a service based on that location information.

When sector information has been used as a basis to describe the location of a mobile station, the description has been inherently vague, because it is not immediately clear where in the sector the mobile station is actually located. For emergency services, this presents a problem, as emergency service personnel may have trouble locating a mobile caller within a given sector. Similarly, some other location-based services may depend on knowing more precisely where a given mobile station is located, so the commercial value of those services may diminish due to the imprecision of the location information.

Therefore, a need exists for an improved method of communicating location in a cellular wireless system, so as to facilitate location-based services.

### SUMMARY

The present invention relates to a method and system for communicating location information in a cellular wireless system. According to an exemplary embodiment of the invention, when a mobile station is operating in a given sector, the mobile station's location can be characterized by reference to a "polygon of influence" drawn for the sector, i.e., by reference to a polygon in which substantially all points are closer to the origin of the sector than to the origins of adjacent sectors. When prompted to report the location of a mobile station, a cellular carrier may thus report an indication of the polygon of influence, such as the geographic coordinates of a point within the polygon of influence.

Thus, in one respect, an exemplary embodiment of the invention can take the form of a method of communicating a geographic location of a given sector in a cellular wireless system, so as to facilitate a location-based service with respect to the given sector. The method can involve establishing a PI-based location to represent the given sector and communicating the PI-based location as a representation of the geographic location of the given sector. A location-based service (such as locating a mobile station in the sector, providing an emergency service, weather reporting, traffic reporting or route planning, for instance) can then be performed based on the PI-based location.

In another respect, an exemplary embodiment of the invention can take the form of a method of communicating mobile station location in a cellular wireless system, where the cellular wireless system has multiple of sectors. The method can involve the functions of (i) determining that a mobile station is located in a given sector, (ii) establishing a PI-based location to represent the given sector, and (iii) communicating the PI-based location as a representation of where the mobile station is located.

The function of establishing the PI-based location for the sector could take various forms. For example, it could be simply querying a table or other data source that correlates an already-created PI-based location with the sector. As another example, it could extend to creating the PI-based location for the sector, including establishing a polygon of influence for the sector.

The function of communicating the PI-based location can also take various forms. For example, it can involve storing the PI-based location in a data store that is accessible (e.g., through suitable messaging) to a recipient entity such as a mobile positioning center and/or a location-based-service provider for instance. As another example, it can involve transmitting the PI-based location to a location-based service provider in response to a request for a location of the mobile station.

In still another respect, an exemplary embodiment of the invention can take the form of a method that involves the functions of (i) determining that a mobile station is located in a given sector of a cellular wireless system, (ii) selecting a PI-based location to represent the given sector and (iii) performing a service based on the PI-based location.

In yet another respect, an exemplary embodiment of the invention can take the form of a system for communicating mobile station location in a cellular wireless system having a number

of sectors, where the mobile station is operating in one of the sectors. The system can include a processor, a data storage medium, and a set of machine language instructions stored in the data storage medium and executable by the processor to establish a PI-based location respectively for each sector. Further, the system can be programmed to communicate that PI-based location to a recipient entity, so as to facilitate a location-based service.

These as well as other aspects and advantages of the present invention will become apparent to those of ordinary skill in the art by reading the following detailed description, with appropriate reference to the accompanying drawings.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

An exemplary embodiment of the present invention is described herein with reference to the drawings, in which:

Figures 1 and 3-11 illustrate a process of creating PI-based locations for the sectors in an exemplary coverage area;

Figure 2 illustrates exemplary radiation patterns from a base station; and

Figure 12 is a simplified block diagram illustrating a network arrangement suitable for carrying out the exemplary embodiment.

### **DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENT**

#### **1. Characterizing Sectors**

In accordance with an exemplary embodiment of the present invention, a cellular wireless carrier or other entity will establish a respective "polygon-of-influence based location" ("PI-based location") to represent each of one or more sectors in a given cellular coverage area. Generally speaking, a PI-based location for a given sector can be defined as a location that is based on a polygon of influence for that sector taken with respect to one or more other sectors.

A polygon of influence for a sector taken with respect to other sectors is a polygon in which substantially all points are closer to the origin of the sector than to the origins of the other sectors. As such, a PI-based location for a given sector can be a geographic characterization of the polygon of influence itself (such as the geographic coordinates of the nodes of the polygon), or of an area drawn with respect to the polygon of influence.

Alternatively, the PI-based location can be geographic coordinates of one or more points within the polygon, such as substantial midpoint of the polygon or of a minimum bounding rectangle drawn around the polygon. Still alternatively, the PI-based location can take other forms, based in some way on a polygon of influence. For instance, a PI-based location can be a street address or intersection that lies at or near the center of a polygon of influence. Other examples are possible as well.

Numerous techniques and tools may be applied in order to establish polygons of influence for the sectors in a coverage area. The process may be executed manually, such as by plotting the locations of base stations and drawing lines to form the polygons. Alternatively, the process may be automated, such as by programming a computer with instructions to read data points representing the locations of base stations, to "draw" the polygons in memory, and to output (e.g., print and/or display) indications of the polygons. Still alternatively, the process may be a combination of manual and automated techniques.

In accordance with the exemplary embodiment, the process will be largely computer-executed. The input to the process can be a data table that lists as records the location coordinates (e.g., latitude/longitude) and azimuth (e.g., angle of propagation from true north) of each sector in the coverage area. Since most base stations will include three 120° antennas (to achieve approximately 360° coverage), the input data table will likely (although not necessarily) list the same base station coordinates for each sector of a given base station, although each of the three sectors will likely have a different azimuth.

The output of the process, in turn, may be a revised data table that reflects representative coordinates of each sector in the coverage area, established according to the exemplary embodiment. This output table may then be used as a basis to characterize the location of a mobile station that is operating in a given sector. Namely, the mobile station may be said to be operating at or near the representative coordinates of the sector. Another output of the process may be a number of objects (object models in computer memory) that define polygons of influence derived for the sectors in the coverage area. A carrier can then conveniently use these objects to display and/or report the polygons of influence.

Referring to Figure 1, a schematic illustration of a cellular coverage area 10 is provided, to help explain how the exemplary embodiment will operate in practice. For simplicity,

coverage area 10 is shown to include five representative base station towers, designated A, B, C, D and E. In reality, the coverage may have more or fewer base station towers. Further, the coverage area is shown to include an outer boundary 12.

Further for simplicity, it will be assumed that each base station tower employs three antennas (or antenna arrangements) to produce three evenly spaced 120° radiation patterns representing respective 120° sectors. Figure 2 schematically depicts (in an idealized form) such radiation patterns 14, 16, 18 (i.e., sectors 14, 16, 18) extending from exemplary base station tower A of Figure 1. Each antenna, and therefore each respective radiation pattern, has a respective azimuth, which is its angle of propagation from true north or from some other reference direction. Figure 2 shows an azimuth  $\theta$  for sector 18 by way of example. It should be understood that other radiation patterns are possible as well.

According to an exemplary embodiment, the process of deriving polygons of influence for the sectors in a coverage area involves first distinguishing the point of origin (or "origin point") of each sector for a given base station, and then drawing a polygon of influence for each sector. The reason to distinguish the point of origin of each sector is to enable a polygon of influence algorithm to readily divide apart the sectors of a given base station, as will become more apparent from the following discussion.

To distinguish the point of origin of each sector for a given base station, a computer can be programmed to plot for each sector a point that extends radially for about 3 feet (or some other relatively small distance, the same for each sector) from the base station, along the azimuth of the sector. Assuming that the input data table lists the same base station coordinates for each of its sectors, this distinguishing-process can thus involve looking at each record in the input table and shifting the sector coordinates by 3 feet along the azimuth indicated in the record. This will usually be a reasonable approximation in any event, since the three antennas on a base station tower usually extend out several feet along their azimuths from the tower.

One way to do this is to apply a computer program written to use the spatial capabilities of a software product such as MapInfo (available from MapInfo Corporation of Troy, New York). The program can be instructed to read a data point (latitude/longitude coordinates) and azimuth from each record of a table. For each record, the program can then be instructed to (i) draw a circle of 3 foot radius around the data point, (ii) draw a line of greater than 3 foot length



extending at the azimuth, and then (iii) find the point of intersection between the circle and line. The program can then be instructed to output that point as the distinguishing point of origin of the sector.

Figure 3 illustrates this process for the sectors of base station A for instance. In the exemplary embodiment, the input data table would list the geographic coordinates of base station tower A as being the location of this sector. A circle 20 of radius 3-feet can then be drawn (i.e., its equation established) around that location. For sector 18, a line 22 can then be drawn extending from the location out at the azimuth  $\theta$  of the sector. Circle 20 and line 22 will then intersect at a point A1, the geographic coordinates of which can be used as the point of origin of the sector. This same process can be repeated for each sector in a coverage area, thereby producing three points around each base station tower, representing the points of origin of the three sectors established by the base station.

Turning now to Figure 4, coverage area 10 is shown with the resulting points of origin indicated for each of the three sectors of each base station A-E. The points of origin of the sectors established by base station A are shown as A1, A2 and A3, the points of origin of the sectors established by base station B are shown as B1, B2 and B3, and so forth.

Provided with a point of origin of each sector in the coverage area, the points can be input into a computer program that is executable to establish a polygon of influence for each point with respect to the other points in the coverage area (a "PI program.") Before applying the PI program, however, it would be best to first simplify the boundaries of the coverage area. In particular, according to the exemplary embodiment, a minimum bounding rectangle ("MBR") can be established around the outer boundary 11 of the coverage area. Assuming that outer boundary is modeled as a bounding polygon defined by a number of nodes having x, y coordinates, the MBR can extend from the minimum x, y coordinates of the bounding polygon to the maximum x, y coordinates of the bounding polygon. (After applying the PI program, the bounding polygon can then be used to clip any polygons of interest that extend beyond it.)

Figure 5 illustrates such an MBR 26 drawn around coverage area 10 of Figure 1. In this figure, the outer boundary 11 of coverage area 10 has been then omitted for clarity. Further, the original base station locations have been omitted for clarity as well. The end result is an MBR encompassing the points of origin of each sector in coverage area 10.

Provided with the MBR encompassing a set of points of origin, the PI program will then proceed to derive a polygon of influence for each point. To do so, an exemplary PI program will be written to execute the following process for each point in the set (i.e., for each sector as to which the program is instructed to establish a polygon of influence):

- (1) Make a list of all connecting-lines that connect the point to each of the other points in the set.
- (2) Make a list of lines to use as potential PI edges, including:
  - (a) Perpendicular bisectors of each connecting-line; and
  - (b) The edges of the MBR.
- (3) Clip all of the potential PI edge lines where they intersect each other. For each potential PI edge line, retain as a PI edge the piece of the PI edge line that is closest to the point. The process of clipping is completed once the potential PI edge lines do not intersect any previously clipped line segment in the clipped PI edge list.
- (4) Connect all of the PI edges, so as to form a polygon that completely encloses the point.

Figures 6-11 illustrate this process in detail for exemplary point A1 in Figure 5, so as to establish a polygon of influence for the corresponding sector 18 of base station A.

As noted, the exemplary PI program first makes a list of all connecting-lines that connect points to each other in the set. Figure 6 illustrates these connecting-lines for point A1. Each line radiates from point A1 to another point in the set. For example, a connecting-line 28 extends from point A1 to point C3.

Next, the PI program makes a list of potential PI edge lines, including (a) perpendicular bisectors of each connecting-line and (b) the edges of the MBR. Figure 7 depicts an exemplary perpendicular bisector 30 of line 28. In turn, Figure 8 depicts perpendicular bisectors of all of the connecting-lines within the MBR.

In turn, the PI program clips all of the potential PI edge lines where they intersect each other. As shown in Figures 9 and 10, the result of this clipping for point A1 is a polygon of influence 32, which the PI program can represent by the coordinates of nodes 32a, 32b, 32c, 32d

and 32e. In the exemplary embodiment, substantially every point within this polygon of influence will be closer to point A1 than to other points within the MBR.

Note that when the PI program performs step (2)(a) of this process, it will inherently include as potential PI edge lines the lines that divide the sectors of a given base station. The reason for this is that a perpendicular bisector of a line that connects two sector points of origin derived with the process above will itself extend radially from the base station, directly between the azimuths of the two sectors. This should generally be the case regardless of whether the sectors all provide 120° coverage.

As output for each sector, the PI program can provide a list of the nodes of the polygon derived for the sector. These nodes can then be provided as input to the MapInfo program, so as to allow the MapInfo program to represent each polygon as an object, which can be displayed or manipulated as desired.

As noted above, the original bounding polygon can be used to clip the polygons produced by the PI program. To do this, the nodes of the original bounding polygon can be input to the MapInfo program, so that the MapInfo program can represent the bounding polygon as an object. Provided with an object representing each polygon of influence and an object representing the original bounding polygon, the MapInfo program can readily clip each polygon of influence to the extent it extends beyond the bounding polygon. The MapInfo program can then output a revised set of nodes for the polygons of influence.

The process described so far for establishing polygons of influence for the sectors in a coverage area is intended to be an example only. Variations are possible. For instance, one variation may be to omit the function of distinguishing the points of origin of each sector for a given base station. Instead, the PI program can receive as input the coordinates of each base station (which is typically, in effect, the point of origin for all sectors of the base station) and can generate as output a polygon of influence around each base station. In turn, for each base station that defines  $N$  sectors of specified azimuths, the PI program or another program can divide each polygon of influence into  $N$  parts. For instance, a program can draw lines extending radially from the base station directly in between each azimuth, and the program can clip the lines at the point that they intersect the polygon of influence. The point of intersection can then function as a common node of each adjacent sector of the base station. Other variations are possible as well.

As noted above, the polygon of influence derived for a given sector may then be used as a basis to characterize the location (e.g., the geographic scope or position) of the sector and thereby as a basis to characterize the location a mobile station known to be operating in the sector. This should function as good characterization, because every point in the polygon of influence for a sector is likely (if not certain) to be closer to the base station that defines the sector than to any other base station in the coverage area. Phrased another way, when a mobile station is operating in a given sector, the mobile station is likely to be located in the polygon of influence for the sector. (Note that, depending on various factors (e.g., signal strength, topography, etc.), this assumption may sometimes fail; but it is believed that the assumption will be valid in most cases. Nevertheless, the present invention functions to *estimate* location, which may be more or less accurate from case to case.)

In the exemplary embodiment, the PI program can conveniently be written to record in the output data table a PI-based location respectively for each sector in a coverage area. The PI-based location for a given sector can take various forms. As an example, the PI-based location can be a list of the geographic coordinates of the nodes that define the polygon of influence for the sector. Conveniently, a recipient of such an indication could model the polygon of influence (using the MapInfo program, for instance) and perhaps display the polygon on a map, so as to clearly understand where the polygon of influence lies and thus where the mobile station is likely positioned. This form of indication would be particularly useful for emergency services, since it would allow emergency service personnel to quickly visualize the area where a mobile 911 caller is likely to be located.

As another example, the PI-based location for each sector can instead take the form of a representative point selected from within the polygon of influence. One such representative point could be the centroid, or center of mass, of the polygon. Typical polygons of influence that will result from the process described above, however, will be complex, having five or more sides, and it is computationally difficult to determine the center of mass of a complex polygon. Therefore, instead of using the center of mass as the representative point, a more simple representative point can be used.

One example of a more simple representative point is the midpoint of a minimum bounding rectangle around the polygon of influence, i.e., the midpoint of a rectangle extending

from the minimum x and y coordinates of the polygon of influence to the maximum x and y coordinates of the polygon of influence. In the exemplary embodiment, the PI program can conveniently be written to find the mid-point of such a rectangle by finding the intersection between the diagonals of the rectangle.

Referring to Figure 11, for example, a minimum bounding rectangle 34 has been drawn around polygon of influence 32, and diagonal lines 36, 38 have been drawn through rectangle 34. Those diagonal lines intersect at a point 40. With this exemplary process, the geographic coordinates of point 40 can be used as the PI-based location representing sector 18 of base station A. Other examples are possible as well.

There are advantages to using a single geographic point as the PI-based location to characterize the sector in which the mobile station is operating. For one, it is easy to store the location coordinates of the representative point. Provided with an input data table described above, the output data table can take the same form, but the location coordinates listed for each sector can be the newly derived representative point of the polygon of influence for the sector. Further, many existing location-based services are designed to receive a single location point (e.g., latitude/longitude coordinates) indicative of the mobile station's location. The representative point selected from within a polygon derived according the process described above can thus readily accommodate those services.

In accordance with the exemplary embodiment, a cellular carrier or other entity can perform the process described above periodically or in response to various other triggering events, so as to regularly update or maintain the PI-based location of each sector in the carrier's coverage area. For example, a carrier can execute the programs described above once a day. As another example, whenever a substantial change occurs in a carrier's coverage area (such as when a new base station is added, or when new buildings are erected), the carrier can execute the process described above.

## **2. Communicating PI-based Location**

A PI-based location can be used as a representation of the geographic location of a sector and/or as a representation of the geographic location of a mobile station operating in a sector. The PI-based location can therefore be used to facilitate a location based service with respect to a

given sector, such as a location-based service with respect to a mobile station operating in the sector.

PI-based location information can be used in a variety of ways. For example, a carrier or other entity can push (e.g., send) a PI-based location to location-based-service provider. As another example, the carrier or other entity can make PI-based location information available to be pulled (e.g., read) by a location-based-service provider. As still another example, the carrier or other entity can itself use the PI-based location information to carry out a location-based service.

**a. Exemplary Network Architecture**

Referring now to Figure 12, there is shown a simplified block diagram of a communication system 100 in which the exemplary embodiment can be employed. It should be understood that this and other arrangements and processes described herein are set forth for purposes of example only, and other arrangements and elements (e.g., machines, interfaces, functions, orders of elements, etc.) can be used instead and some elements may be omitted altogether. Further, as in most telecommunications applications, those skilled in the art will appreciate that many of the elements described herein are functional entities that may be implemented as hardware, firmware and/or software, and as discrete components or in conjunction with other components, in any suitable combination and location.

By way of example, system 100 is shown to include a mobile switching center ("MSC") 102 coupled with a base station controller ("BSC") 104, which is coupled in turn with a base transceiver station ("BTS") 106. The BTS includes one or more antenna elements arranged to produce radiation patterns defining one or more sectors. An exemplary mobile station ("MS") 108 then operates within a given sector and communicates via an air interface 110 with BTS 106, and in turn via the BSC 104 with MSC 102.

As further illustrated by way of example, MSC 102 is coupled by a signaling link 112 to a mobile positioning center ("MPC") 114. As defined by J-STD-036, the MPC functions to retrieve, forward, store and control position data. As such, the MPC can be based on a location information platform, such as the "local.info" service platform available from SignalSoft Corp. of Boulder, Colorado. Further, both MPC 114 and MSC 102 are preferably programmed with an

industry standard message set such as that defined by TIA/EIA/IS-41D ("IS-41") and J-STD-036, so as to facilitate communication over link 112 between MPC 114 and MSC 102.

An example of one of the messages that MSC 102 can send to MPC 114 in the exemplary embodiment is an "Origination Request INVOKE" or "ORREQ" message, which generally functions to request call processing assistance on behalf of a registered MS. An ORREQ message can carry a number of parameters, one of which is an identification of the MS (such as a mobile identification number ("MIN")) and another of which is a "LocationAreaID" parameter that indicates the BTS currently serving a mobile station and the sector in which the mobile station is operating. The MPC can then apply service logic send an "Origination Request Return Result" or "orreq" message back to the MSC, indicating a service treatment such as where to route the call.

MPC 114 can be implemented as one or more computer applications and database functions programmed on an SCP such as the Integrated Service Control Point ("ISCP") made by Telcordia Technologies, Inc. Further, another SCP may be positioned along signaling link 112, so that MSC 102 communicates with the other SCP, and the other SCP in turn communicates with MPC 114.

Conventionally, MSC 102 is further coupled via a signaling link 120 with an HLR 122, which stores service qualifications and other information concerning mobile stations. In normal operation, when a mobile station such as MS 108 enters into a new sector, MSC 102 sends a registration notification ("REGNOT") message via link 120 to HLR 122. According to IS-41, of the parameters in the REGNOT message is the LocationAreaID, which the HLR stores in a profile to facilitate terminating calls to the mobile station.

In exemplary system 100, MSC 102 is further coupled by a trunk 124 with an emergency services network 126, which includes an Emergency Services Network Entity ("ESNE") 128 and a PSAP 130. ESNE 128 functions effectively as a local exchange carrier ("LEC") switch (such as an SSP) for receiving call traffic into the emergency services network and for routing that call traffic to one or more PSAPs such as PSAP 130. Each PSAP, in turn, may be a 911 center or other point that receives emergency services calls. Thus, ESNE 128 can engage in call-setup signaling with MSC 102 so as to set up calls to PSAP 130.

Additionally, MSC 102 is shown coupled by a trunk 132 with an enhanced services platform ("ESP") 134. ESP 132 can be a programmed computer or more complex platform, such a platform programmed on a service node from INFONXX, Inc. of Bethlehem, Pennsylvania, or InterVoice-Brite Systems, Inc. of Dallas, Texas. As such, ESP 132 can include an integrated voice response unit ("IVRU") for interacting with a caller, and it can include suitable interfaces and logic for communicating with MSC 102.

Still further, MSC 102 is shown coupled by a link 136 with a location-based-service provider platform 138. Link 136 could take various forms. As an example, the link could be an Internet connection. As another example, the link could be a short message service ("SMS") path including a short message service center ("SMSC," not shown) and perhaps a bulk message gateway ("BMG," not shown) for communicating short text messages.

Yet further, BSC 104 is shown coupled to a packet data serving node ("PDSN") 140, which provides connectivity to the Internet 142. Another location-based-service provider platform 144 is then shown linked with the Internet 142 as well.

**b. Maintenance of Location Information**

In accordance with the exemplary embodiment, MPC 114 can be arranged to periodically generate and maintain data indicating a PI-based location for each sector in a carrier's coverage area. Since MPC 54 is typically a program application executed on an SCP, the process of providing this added functionality should be a straightforward revision of the MPC program and/or addition of other program modules as desired.

In particular, the MPC can be provided with an input table that lists for each sector in the coverage area (i) the LocationAreaID of the sector, (ii) the geographic coordinates of sector, namely of the BTS, and (iii) the azimuth of the sector. Applying the process described above, the MPC can then produce an output table 146 that indicates for each sector (i) the LocationAreaID of the sector and (ii) a PI-based location of the sector, and the MPC can store the output table in memory or elsewhere (internally and/or externally). The output table can be referred to as a "PI-based-location table."

In the exemplary embodiment, when the MPC receives an ORREQ that carries a LocationAreaID parameter, the MPC can then readily refer to the PI-based-location table to determine the PI-based location for the sector in which the mobile station is operating. The MPC



can then push the PI-based location to a location-services provider. Alternatively, an authorized location-services provider can pull PI-based location information from the table. Intermediate messaging entities (not shown) may be provided as well.

In addition, MPC 114 can be arranged to maintain a table 148 indicating the location of registered mobile stations, such as MS 108. Table 148 can list, for each mobile station, the mobile station's MIN (or an encrypted version of the MIN) and a corresponding LocationAreaID, which can be translated into a PI-based location by reference to table 146. Alternatively, table 148 can itself list the MIN (or encrypted MIN) and a corresponding PI-based location.

To populate table 148, HLR 122 or another suitable entity can be programmed to send a signaling message to MPC 114 via a link 150 whenever HLR 122 receives a REGNOT message providing a LocationAreaID for a mobile station. The signaling message can identify the MIN of the mobile station and the LocationAreaID. MPC 114, in turn, can be programmed to store the MIN (or establish and store an encrypted version of the MIN) and the corresponding LocationAreaID and/or PI-based location (per table 146) in table 148. Alternatively or additionally, each time MPC 114 receives an ORREQ message or other message that identifies a mobile station's current LocationAreaID, the MPC can store the mobile station's MIN (or encrypted MIN) and LocationAreaID and/or PI-based location in table 148.

According to the exemplary embodiment, an authorized location-services platform, such as platform 138 or 144, can then signal to MPC 114 to determine where a particular mobile station is located, or to find out which mobile stations are located in a particular geographic area (such as in an area covering one or more sectors). MPC 114 can then query table 146 and/or table 148, and respond accordingly, so as to facilitate a location-based service.

**c. Example: MPC pushes PI-based location to PSAP**

As noted above, one example of a location-based-service provider is an emergency service center, which can use location to help locate a mobile emergency caller. Referring to Figure 12, the process of using a PI-based location to help facilitate emergency services can operate as follows.

First, a user of a mobile station, such as MS 108, enters the digits "911" and presses "SEND", "TALK" or another designated key on the mobile station to cause those digits to pass via BTS 106 and BSC 104 to MSC 102. MSC 102 will then receive those dialed digits and begin

to process the call. In particular, MSC will apply a set of call-processing program logic to analyze the dialed digits and to then physically (or logically) connect the call from MS 108 to the dialed destination, PSAP 130 (or more generally ESN 126).

In accordance with J-STD-036, the call-processing logic will include a trigger point at which the MSC will recognize that the digits dialed are "911" and that the MSC should pause call processing and signal up to MPC 114. MSC 102 will thus pause call processing and send an ORREQ message up to MPC 114, which will carry the mobile station's MIN and the LocationAreaID indicating the sector in which the MS is currently operating.

When MPC 114 receives the ORREQ, the MPC will read the LocationAreaID from the ORREQ and then query the PI-based-location table so as to determine the PI-based location that represents the sector in which the MS is operating.

Depending on the arrangement, MPC 114 may then send an "orreq" response message to MSC 102, providing MSC 102 with the PI-based location as an indication of where MS 108 is located. (In this regard, J-STD-036 defines a geographic position (GEOPOS) parameter in an orreq response message, which can be used to convey a latitude/longitude position; other parameters could be defined as well.) MSC 102 would then send a call-setup message (e.g., an ISUP Initial Address Message ("IAM")) to the emergency services network, which would carry as a parameter the PI-based location of MS 108 as returned by MPC 114. Thus, when PSAP 130 receives the call, PSAP 130 will already have the PI-based location as an indication of where the caller is located, thereby enabling emergency services personnel to better assist the caller.

Alternatively, the MPC can itself signal to the emergency services network (via an Emergency Services Message Entity (not shown)), providing PSAP 130 with the PI-based location as an indication of where MS 108 is located, together with a transaction identifier, such as the mobile station's MIN. And the MPC may further send an orreq response to MSC 102. MSC 102 would then connect the call to PSAP 130, and PSAP 130 would associate the location provided by MPC 114 with the call connected from MSC 108 (by reference to the transaction identifier, for instance), thereby establishing the location of the caller.

**d. Example: MPC pushes PI-based location to ESP**

In the exemplary embodiment, ESP 134 can also function as a location-based-service provider. For instance, ESP 134 could be programmed to provide a location-based directory

service that provides a mobile caller with information about service establishments located near the caller. A process of facilitating such a service using PI-based location information may operate as follows.

First, a user of MS 108 dials a special feature code, such as "#76" for instance. When MSC 102 receives the feature code, it begins call processing and encounters a trigger point, which causes MSC 102 to send an ORREQ to MPC 114, conveying the MIN and LocationAreaID.

When MPC 114 receives the ORREQ, the MPC reads the LocationAreaID from the ORREQ and then queries the PI-based-location table so as to determine the PI-based location that represents the sector in which the MS is operating. The MPC then records the mobile station's MIN (or encrypted MIN) and PI-based location in table 148. Further, the MPC sends an orreq response message to MSC 102, instructing MSC 102 to route the call to ESP 134. MSC 102 will thus route the call via trunk 132 to ESP 134.

When ESP 134 receives the call, ESP 134 sends a signaling message to MPC 114 via a link 152, requesting the location of the caller. In an exemplary arrangement, link 152 can be an ISDN link or an Internet link or could take other forms. Further, the location request message could be an XML formatted request message. An MPC daemon (not shown) or other entity can receive the request message and forward it to the MPC.

Upon receipt of the location request message, the MPC queries table 148 and/or table 146 to determine the PI-based location of MS 108. The MPC then sends a response message to ESP 134, providing the PI-based location. ESP 134 then performs a directory service based on that location. For instance, the user of MS 108 may request an indication of nearby pizza restaurants, and ESP 134 may query a directory database to find pizza restaurants located within a 3 mile radius of the PI-based location.

**e.     Example: Location-Based Service Platform  
          Pulls PI-Based Location Information from MPC**

Location-based-service platforms 138, 144 could also use PI-based location information to facilitate providing a location-based service. For example, MS 108 could engage in a data session via PDSN 140 and Internet 142 with platform 144. Alternatively, MS 108 could engage in a data session via link 136 with platform 138. Once connected, the platform can then ask

MPC 114 for the location of MS 108, and MPC 114 can responsively provide the PI-based location.

For instance, upon initiation of the data session, the platform could have an encrypted MIN identifying MS 108. The platform can then send a location-request message to MPC 114 via a link 154 158, providing MPC 114 with the encrypted MIN. And MPC 114 can query table 146 and/or table 148 so as to translate the encrypted MIN into a PI-based location indicative of where MS 108 is located and then respond with a signaling message to platform 144, providing the PI-based location. Platform 144 can then perform a service for MS 108 based on that PI-based location.

As another example, a location-based-service platform such as platform 138 could query MPC to determine the MINs (or encrypted MINs) of some or all mobile stations that are currently located in a designated area. The area could be defined in any way, and the MPC could convert the area to geographic coordinates by reference to a mapping table. By reference to tables 146 and/or 148, the MPC can then determine which mobile stations are operating in a sector having a PI-based location in the designated area. And the MPC may then respond to platform 138, providing a list of MINs (or encrypted MINs) of some or all of those mobile stations. The platform can then perform a service with respect to all of those mobile stations.

For instance, platform 138 can be programmed to function as an e-coupon or electronic advertisement provider. The platform can thus query MPC 114 to find all mobile stations located in an area of commercial interest to a particular retailer, and the platform can then send coupons or advertisements, via link 136, to those mobile stations. Other examples are possible as well.

### **3. Conclusion**

An exemplary embodiment of the present invention has been described above. Those skilled in the art will understand, however, that changes and modifications may be made to this embodiment without departing from the true scope and spirit of the present invention, which is defined by the claims. Further, it should be understood that the functions recited in the claims may occur in an order other than listed, unless noted otherwise.